NSN 5305-01-093-7022

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-093-7022 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.470 inches and 0.562 inches **Fastener Length:** Between 0.532 inches and 0.562 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.303 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.1562 inches and 0.1587 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Color: Black Material: Steel **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13929 cl 1 military specification single treatment response **Thread Series Designator:** Unrf **Specification Data:**

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

NSN 5305-01-093-7022

Socket Head Cap Screw - Page 2 of 2



	• -		
In	ıŧ	()t	Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13929 spec.