Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-094-2477

Thread Direction	n:
Right-hand	
Thread Length:	
Between 0.168 i	nches and 0.198 inches
Fastener Lengt	h:
Between 0.490 i	nches and 0.510 inches
Head Style:	
Pan	
First Diameter	From Head:
Between 0.067 i	nches and 0.072 inches
Distance From	Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.312 i	nches and 0.332 inches
Internal Drive S	ityle:
Cross recess typ	be 1
Thread Diamete	er:
0.112 inches	
Thready Qty Pe	r Inch (tpi):
40	
Externally Relie	eved Body Diameter Quantity:
1	
Product Name:	
Navy special pro	oject
Material:	
Steel comp 301	or steel comp 302 or steel comp 303 or steel comp 303f or steel comp 303se or steel comp 304 or steel comp 304l or
steel comp 305	or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or
steel comp 316	or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel
comp 348 or ste	eel comp 385
Surface Treatm	ent:
Passivate	
Surface Treatm	ent Specification:
Qq-p-35 federal	specification single treatment response
Thread Series I	Designator:
Unc	
Shelf Life:	
N/a	
Unit Of Measur	e:
Demilitarizatior	1:
No	
Fiig:	
A003b0	