## NSN 5305-01-094-5963

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-094-5963 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.143 inches **Fastener Length:** 0.319 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.121 inches and 0.124 inches **Head Height:** 0.056 inches **First Diameter From Head:** Between 0.095 inches and 0.097 inches **Second Diameter From Head:** Between 0.121 inches and 0.124 inches **Third Diameter From Head:** 0.187 inches **Fourth Diameter From Head:** 0.188 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.030 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.114 inches and 0.119 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.145 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 0.176 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 4

Material:

Steel comp 303

**Material Specification:** 

Astm a582 assn standard single material response

## NSN 5305-01-094-5963

Externally Relieved Body Screw - Page 2 of 2



Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0