

View Online at <https://aerobasegroup.com/nsn/5305-01-095-3294>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.337 inches and 0.387 inches

**Fastener Length:**

Between 0.472 inches and 0.502 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.258 inches and 0.305 inches

**Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.115 inches and 0.135 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Surface Finish:**

32.0 microinches threads

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5731 national std/spec single material response or ams 5732 national std/spec single material response or ams 5737 national std/spec single material response or ams 5853 national std/spec single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1581 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0