NSN 5305-01-095-5706

Between 0.422 inches and 0.516 inches

Between 0.484 inches and 0.516 inches

Thread Class:

Right-hand

Thread Length:

Thread Direction:

Fastener Length:

За

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-095-5706

Head Style:
Flat chamfer
Head Diameter:
Between 0.303 inches and 0.312 inches
Head Height:
Between 0.185 inches and 0.190 inches
Hole Diameter:
Between 0.044 inches and 0.050 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.190 inches
Width Across Flats:
Between 0.1562 inches and 0.1587 inches
Hole Quantity:
6
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
32
Min. Tomaile Chromath (mails
Min. Tensile Strength (psi):
160000 pounds per square inch
160000 pounds per square inch
160000 pounds per square inch Hole Configuration Style:
160000 pounds per square inch Hole Configuration Style: Round internal hexagon
160000 pounds per square inch Hole Configuration Style: Round internal hexagon Material:
160000 pounds per square inch Hole Configuration Style: Round internal hexagon Material: Iron alloy 660
160000 pounds per square inch Hole Configuration Style: Round internal hexagon Material: Iron alloy 660 Material Specification:
160000 pounds per square inch Hole Configuration Style: Round internal hexagon Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response
160000 pounds per square inch Hole Configuration Style: Round internal hexagon Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment:
160000 pounds per square inch Hole Configuration Style: Round internal hexagon Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate
160000 pounds per square inch Hole Configuration Style: Round internal hexagon Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
160000 pounds per square inch Hole Configuration Style: Round internal hexagon Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
160000 pounds per square inch Hole Configuration Style: Round internal hexagon Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:

NSN 5305-01-095-5706

Socket Head Cap Screw - Page 2 of 2



-			
٠.	hΔ	Iŧ.	ife:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0