NSN 5305-01-095-6333

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-095-6333 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.160 inches and 0.200 inches **Fastener Length:** Between 0.850 inches and 0.880 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Hardness Rating:** Between 39.0 rockwell c and 43.0 rockwell c **Screw Material:** Steel comp 347 or steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 **Screw Material Specification:** Qq-s-763 federal specification all material responses **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Special Features:** Undercut body between head and thread 0.090 in. To 0.093 in. Diameter by 0.680 in. To 0.690 in. Long **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No Fiig:

A500d0

Demilitarization: