## NSN 5305-01-095-7930

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-095-7930 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.444 inches and 0.494 inches **Fastener Length:** Between 2.454 inches and 2.484 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.497 inches and 0.508 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.081 inches first hole **Internal Drive Style:** High-torque **End Application:** Aircraft, eagle f-15 **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.990 inches and 2.010 inches Thready Qty Per Inch (tpi): 28 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 2.333 inches first hole and 2.373 inches first hole **Surface Finish:** 32.0 microinches threads Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response

Unjf

**Thread Series Designator:** 

## NSN 5305-01-095-7930

Close Tolerance Screw - Page 2 of 2



-			 
٠.	hΔ	Iŧ.	ife:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0