## NSN 5305-01-096-3060



Machine Screw - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-096-3060 **Thread Direction:** Right-hand Thread Length: Between 0.264 inches and 0.274 inches **Fastener Length:** Between 0.433 inches and 0.443 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.359 inches and 0.385 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches **Nonstandard Thread Pitch Diameter:** +0.1644/+0.1667 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 135000 pounds per square inch **Hardness Rating:** Between 30.0 rockwell c and 38.0 rockwell c **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Screw Material:** Steel comp 601 **Screw Material Specification:** Ams 6304 assn standard single material response **Screw Surface Treatment:** Nickel and cadmium **Screw Surface Treatment Specification:** Ams 2416 assn standard single treatment response **Thread Series Designator:** Unf

| Shelf Life:       |
|-------------------|
| N/a               |
| Unit Of Measure:  |
|                   |
| Demilitarization: |
| No                |
| Fiig:             |
| A500d0            |
|                   |