NSN 5305-01-096-3775

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-096-3775

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.337 inches and 0.403 inches
Fastener Length:
Between 0.672 inches and 0.718 inches
Head Style:
Pan
Head Diameter:
Between 0.256 inches and 0.270 inches
Head Height:
Between 0.087 inches and 0.089 inches
Locking Feature: Patch threads or pollet threads or strip threads
Patch threads or pellet threads or strip threads Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Material:
Steel comp 4037 fastener or steel comp 8630 fastener
Material Specification:
Ams 6300 assn standard 1st material response fastener or mil-s-6050 military specification 2nd material response fastener
Surface Treatment:
Cadmium fastener and chromate fastener
Surface Treatment Specification:
Qq-p-416 type 2 cl 3 federal specification single treatment response fastener
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No No

NSN 5305-01-096-3775

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6050 spec.