

View Online at <https://aerobasegroup.com/nsn/5305-01-096-3775>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.337 inches and 0.403 inches

Fastener Length:

Between 0.672 inches and 0.718 inches

Head Style:

Pan

Head Diameter:

Between 0.256 inches and 0.270 inches

Head Height:

Between 0.087 inches and 0.089 inches

Locking Feature:

Patch threads or pellet threads or strip threads

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

Material:

Steel comp 4037 fastener or steel comp 8630 fastener

Material Specification:

Ams 6300 assn standard 1st material response fastener or mil-s-6050 military specification 2nd material response fastener

Surface Treatment:

Cadmium fastener and chromate fastener

Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response fastener

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6050 spec.