NSN 5305-01-096-7350

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-096-7350 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.506 inches and 0.556 inches **Fastener Length:** Between 1.266 inches and 1.296 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.429 inches and 0.477 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Internal Drive Style:** High-torque **End Application:** Harrier; aircraft, eagle f-15 **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.740 inches and 0.760 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** Between 99.5 degrees and 100.5 degrees **Special Features:** Cetyl alcohol application per mil-l-87132, type 1, grade b Material: Steel comp xm-13 **Material Specification:** 23-112 fscm 76301 mfr ref single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Mil-c-83488 type 2 class 3 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-01-096-7350

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.