NSN 5305-01-097-0321

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-097-0321 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.440 inches and 0.470 inches **Fastener Length:** Between 2.940 inches and 2.970 inches **Head Style:** Pan **Head Diameter:** 0.322 inches **Head Height:** 0.115 inches **First Diameter From Head:** 0.120 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 2.500 inches **Internal Drive Style:** Cross recess type 1 **End Application:** An/alq-99 (v) **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity: Special Features:** Cone point Material: Stainless steel or steel **Material Specification:** Qq-s-763, 300 series federal specification 1st material response or 66, 300 series federal standard 1st material response or comp 16-18 or 18-8 assn standard 2nd material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, e300 military specification single treatment response

N/a

Unc

Shelf Life:

Thread Series Designator:

NSN 5305-01-097-0321

Externally Relieved Body Screw - Page 2 of 2



Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.