NSN 5305-01-097-0934

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-097-0934

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.469 inches
Fastener Length:
1.781 inches
Head Style:
Pan no. 2
Head Diameter:
Between 0.357 inches and 0.373 inches
Head Height:
Between 0.122 inches and 0.133 inches
Hole Diameter:
0.093 inches
Internal Drive Style:
Cross recess type ii
Thread Diameter:
0.190 inches
Hole Quantity:
1
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
Between 26.0 rockwell c and 32.0 rockwell c
Screw Material:
Steel
Screw Material Specification:
Mil-s-8695 military specification single material response or mil-s-6050 military specification single material response
Screw Surface Treatment:
Cadmium
Screw Surface Treatment Specification:
Qq-p-416, type 2, class 3 federal specification single treatment response
Special Features:
Drilled hole in shank 1.580 inches from head largest bearing surface to shank hole center.
Thread Series Designator:
Unf
Shelf Life:
N/a

NSN 5305-01-097-0934

Machine Screw - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-8695 spec.