

View Online at <https://aerobasegroup.com/nsn/5305-01-097-5842>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.843 inches and 0.893 inches

Fastener Length:

Between 2.603 inches and 2.633 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.645 inches and 0.672 inches

Grip Diameter:

Between 0.6235 inches and 0.6245 inches

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.625 inches

Grip Length:

Between 1.740 inches and 1.760 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

220000 pounds per square inch

Countersink Angle:

Between 59.75 degrees and 60.25 degrees

Surface Finish:

32.0 microinches threads

Special Features:

Bearing surface of head grooved to 0.472 in. Min, 0.474 in. Maximum dia. 0.115 in. Min, 0.120 in. Maximum from top of head

Material:

Steel comp h11

Material Specification:

Ams 6485 assn standard single material response

Surface Treatment:

Nickel and cadmium

Surface Treatment Specification:

Ams 2416 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0