## NSN 5305-01-097-7892

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-097-7892 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.922 inches and 2.500 inches **Fastener Length:** Between 5.922 inches and 6.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 1.107 inches and 1.125 inches **Head Height:** Between 0.740 inches and 0.750 inches **Locking Feature:** Patch threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.750 inches Width Across Flats: 0.625 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch Material: Steel **Surface Treatment:** Zinc **Surface Treatment Specification:** Qq-z-325 type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 6 type

Shelf Life:

N/a

## NSN 5305-01-097-7892

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0