

View Online at <https://aerobasegroup.com/nsn/5305-01-097-8218>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.382 inches and 0.432 inches

**Fastener Length:**

Between 0.704 inches and 0.734 inches

**Head Style:**

Flat countersunk undercut

**Head Diameter:**

Between 0.3765 inches and 0.3813 inches

**Head Height:**

Between 0.0439 inches and 0.0459 inches

**Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.302 inches and 0.322 inches

**Thread Qty Per Inch (tpi):**

32

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Surface Finish:**

32.0 microinches threads

**Special Features:**

Furnished with one o ring

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Aluminum and chromate

**Surface Treatment Specification:**

Mil-c-83488 type 2 cl 3 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-83488 spec.