## NSN 5305-01-097-8938

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-097-8938 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.627 inches and 0.740 inches **Fastener Length:** Between 0.908 inches and 0.938 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.600 inches and 0.656 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches Width Across Flats: 0.188 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 36.0 rockwell c and 45.0 rockwell c **Countersink Angle:** Between 80.0 degrees and 82.0 degrees Material: Steel **Material Specification:** 66 federal standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unf

Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

## NSN 5305-01-097-8938

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0