NSN 5305-01-097-9408

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-097-9408 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.348 inches **Fastener Length:** Between 0.209 inches and 0.219 inches **Head Style:** Fillister **Head Diameter:** Between 0.437 inches and 0.439 inches **Head Height:** Between 0.209 inches and 0.219 inches **Shoulder Diameter:** 0.3085 inches first shoulder and 0.3105 inches first shoulder **Shoulder Length:** 0.290 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 32.0 rockwell c and 35.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel comp 416 **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072 e300 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: **Unit Of Measure:**

N/a **Demilitarization:** No

NSN 5305-01-097-9408

Shoulder Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.