NSN 5305-01-098-1514



Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-098-1514 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.672 inches and 0.766 inches **Fastener Length:** Between 0.734 inches and 0.766 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Locking Feature:** Patch threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1742 professional/industrial association standard Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-098-1514

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0