

View Online at <https://aerobasegroup.com/nsn/5305-01-098-3784>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.409 inches and 0.620 inches

**Fastener Length:**

Between 0.719 inches and 0.750 inches

**Head Style:**

Flat countersunk undercut

**Head Diameter:**

Between 0.775 inches and 0.875 inches

**Head Height:**

Between 0.130 inches and 0.156 inches

**Locking Feature:**

Patch threads or strip threads

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.500 inches

**Thready Qty Per Inch (tpi):**

13

**Min. Tensile Strength (psi):**

60000 pounds per square inch

**Countersink Angle:**

Between 80.0 degrees and 82.0 degrees

**Material:**

Steel fastener

**Material Specification:**

66 federal standard single material response fastener

**Surface Treatment:**

Cadmium fastener and chromate fastener

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 3 federal specification single treatment response fastener

**Thread Series Designator:**

Unc

**Specification Or Standard:**

3 type and 2c style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0