## NSN 5305-01-098-7194

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-098-7194 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.938 inches and 1.000 inches **Fastener Length:** 1.000 inches **Head Style:** Hexagon **Head Height:** Between 0.103 inches and 0.120 inches Width Between Flats: Between 0.305 inches and 0.312 inches **Internal Drive Style:** Slot **End Application:** Mrap buffalo mk2a2 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 60000 pounds per square inch **Screw Material:** Steel **Screw Material Specification:** Qq-s-637 federal specification single material response or 66 federal standard single material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 ty2 cl3 federal specification single treatment response **Thread Series Designator:** Unf **Specification Or Standard:** 1 type and 10s style Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-01-098-7194

Machine Screw - Page 2 of 2



Fiig:

A500d0