NSN 5305-01-098-7203

Socket Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-098-7203 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.620 inches and 0.750 inches **Fastener Length:** Between 0.720 inches and 0.750 inches **Head Style:** Watertight **Head Diameter:** Between 0.473 inches and 0.517 inches **Head Height:** Between 0.162 inches and 0.175 inches **Locking Feature:** Patch threads or pellet threads or strip threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 **Special Features:** Furnished with one o-ring Material: Steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7 **Material Specification:** Qq-s-763 federal specification 1st material response or qq-s-763 federal specification 2nd material response or qq-s-763 federal specification 3rd material response or astm a493 assn standard 1st material response or astm a493 assn standard 2nd material response or astm a493 assn standard 3rd material response or astm a493 assn standard 4th material response or astm a493 assn standard 5th material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

Fiig:

No

Unit Of Measure:

Demilitarization: