

View Online at <https://aerobasegroup.com/nsn/5305-01-099-6054>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.140 inches

**Fastener Length:**

0.325 inches

**Head Style:**

Fillister

**Head Diameter:**

0.173 inches

**Head Height:**

0.098 inches

**First Diameter From Head:**

0.075 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.185 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Hardness Rating:**

36.0 rockwell c and 38.0 rockwell c

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758 cond c and 4 military specification single material response

**Surface Treatment:**

Passivate head

**Surface Treatment Specification:**

Mil-f-14072 -262a military specification single treatment response head

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6758 spec.