NSN 5305-01-099-6054

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-099-6054 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.140 inches **Fastener Length:** 0.325 inches **Head Style:** Fillister **Head Diameter:** 0.173 inches **Head Height:** 0.098 inches **First Diameter From Head:** 0.075 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.185 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Hardness Rating: 36.0 rockwell c and 38.0 rockwell c **Externally Relieved Body Diameter Quantity:** Material: Steel comp 4130 **Material Specification:** Mil-s-6758 cond c and 4 military specification single material response **Surface Treatment:** Passivate head **Surface Treatment Specification:** Mil-f-14072 -262a military specification single treatment response head **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-099-6054

Externally Relieved Body Screw - Page 2 of 2



_		••	• •				
n	em	ш	112	riz	2 †1	n	٠.

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.