NSN 5305-01-099-7203

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-099-7203 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.000 inches **Fastener Length:** Between 4.980 inches and 5.020 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.188 inches and 0.190 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch Material: Steel **Surface Treatment:** Nickel **Surface Treatment Specification:** Mil-c-26074, cl 1 gr b military specification single treatment response **Thread Series Designator:** Unrf **Specification Or Standard:** 6 type **Departure From Cited Designator:**

As modified by surface finish

Shelf Life:

N/a

NSN 5305-01-099-7203

Socket Head Cap Screw - Page 2 of 2



U	nit	Of	Measure:
---	-----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-26074 spec.