

View Online at <https://aerobasegroup.com/nsn/5305-01-100-5150>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.690 inches

Fastener Length:

1.500 inches

Head Style:

Hexagon extended washer

Head Height:

0.103 inches

Width Between Flats:

Between 0.244 inches and 0.250 inches

Extended Washer Diameter:

Between 0.322 inches and 0.348 inches

Extended Washer Thickness:

0.045 inches

Washer Quantity:

1

Internal Drive Style:

W/o internal drive

End Application:

Crane high speed, high mobilite (tam) b0443; cargo system, 463l

Thread Diameter:

0.164 inches

Thready Qty Per Inch (tpi):

32

Hardness Rating:

44.0 rockwell c primary washer and 48.0 rockwell c primary washer

Primary Washer Outside Diameter:

Between 0.370 inches and 0.380 inches

Primary Washer Style:

Spring tension

Primary Washer Material Thickness:

0.025 inches

Material:

Steel fastener

Material Specification:

Sae 1050 assn standard 2nd material response primary washer

Surface Treatment:

Cadmium and dichromate

Surface Treatment Specification:

G-4252-m code 30d72 mfr ref single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0