

View Online at <https://aerobasegroup.com/nsn/5305-01-100-5150>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.690 inches

**Fastener Length:**

1.500 inches

**Head Style:**

Hexagon extended washer

**Head Height:**

0.103 inches

**Width Between Flats:**

Between 0.244 inches and 0.250 inches

**Extended Washer Diameter:**

Between 0.322 inches and 0.348 inches

**Extended Washer Thickness:**

0.045 inches

**Washer Quantity:**

1

**Internal Drive Style:**

W/o internal drive

**End Application:**

Crane high speed, high mobilite (tam) b0443; cargo system, 463l

**Thread Diameter:**

0.164 inches

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

44.0 rockwell c primary washer and 48.0 rockwell c primary washer

**Primary Washer Outside Diameter:**

Between 0.370 inches and 0.380 inches

**Primary Washer Style:**

Spring tension

**Primary Washer Material Thickness:**

0.025 inches

**Material:**

Steel fastener

**Material Specification:**

Sae 1050 assn standard 2nd material response primary washer

**Surface Treatment:**

Cadmium and dichromate

**Surface Treatment Specification:**

G-4252-m code 30d72 mfr ref single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0