## NSN 5305-01-100-7835

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-100-7835

Thread	Class:

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

0.312 inches

#### Fastener Length:

0.687 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.419 inches and 0.437 inches

#### **Head Height:**

Between 0.170 inches and 0.175 inches

#### Shoulder Diameter:

0.3085 inches first shoulder and 0.3105 inches first shoulder

#### Shoulder Length:

0.370 inches first shoulder and 0.380 inches first shoulder

#### Internal Drive Style:

Hexagon

### **Thread Diameter:**

0.250 inches

#### Width Across Flats:

0.156 inches

#### Thready Qty Per Inch (tpi):

20

#### Shoulder Shape:

Round first shoulder

#### Material:

Steel comp 304

#### **Material Specification:**

Qq-s-763 federal specification single material response

#### Surface Treatment:

Passivate

#### Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

#### **Thread Series Designator:**

Unc

Shelf Life:

N/a

## Unit Of Measure:

---

# NSN 5305-01-100-7835

Shoulder Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.

