## NSN 5305-01-100-7835

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-100-7835 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.312 inches **Fastener Length:** 0.687 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.419 inches and 0.437 inches **Head Height:** Between 0.170 inches and 0.175 inches **Shoulder Diameter:** 0.3085 inches first shoulder and 0.3105 inches first shoulder **Shoulder Length:** 0.370 inches first shoulder and 0.380 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: 0.156 inches Thready Qty Per Inch (tpi): 20 **Shoulder Shape:** Round first shoulder Material: Steel comp 304 **Material Specification:** Qq-s-763 federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-s-5002 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-01-100-7835

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.