NSN 5305-01-100-8789

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-100-8789 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.450 inches and 0.500 inches **Fastener Length:** 0.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches **Hole Diameter:** Between 0.033 inches and 0.039 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: 0.188 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch **Hole Configuration Style:** Round internal hexagon **Criticality Code Justification:** Zzzy **Product Name:** Navy special project

Material:

Stainless steel

NSN 5305-01-100-8789

Socket Head Cap Screw - Page 2 of 2



| Surface Treatment: |
|--|
| Chromium |
| Special Test Features: |
| Special quality control testing |
| Surface Treatment Specification: |
| Qq-c-320 cl 2b federal specification single treatment response |
| Test Data Document: |
| 81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Thread Series Designator: |
| Uns |
| Reference Number Differentiating Characteristics: |
| As differentiated by material which must conform to ships parts control center special quality control provisions |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |