## NSN 5305-01-100-8792

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-100-8792

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.320 inches an	d 0.370 inches
Fastener Length:	
Between 1.080 inches an	d 1.110 inches
Head Style:	
Flat countersunk	
Head Diameter:	
Between 0.337 inches an	d 0.383 inches
Grip Diameter:	
Between 0.1885 inches a	nd 0.1895 inches
Internal Drive Style:	
Cross recess type 1	
Thread Diameter:	
0.190 inches	
Grip Length:	
Between 0.740 inches an	d 0.760 inches
Thready Qty Per Inch (t	bi):
32	
Countersink Angle:	
Between 99.0 degrees ar	d 101.0 degrees
Surface Finish:	
32.0 microinches threads	
Material:	
Steel comp e4340 or ste	el comp 8740
Material Specification:	
Mil-s-5000 military specif	cation 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard
2nd material response	
Surface Treatment:	
Cadmium and chromate	
Surface Treatment Spec	ification:
Qq-p-416 type 2 cl 2 fed	eral specification single treatment response
Thread Series Designat	or:
Unjf	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

## NSN 5305-01-100-8792

Close Tolerance Screw - Page 2 of 2



**Fiig:** A003b0

Mil-std (military Standard):

Mil-s-5000 spec.