

View Online at <https://aerobasegroup.com/nsn/5305-01-101-1412>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.510 inches and 0.546 inches

**Fastener Length:**

Between 0.718 inches and 0.750 inches

**Head Style:**

Flat countersunk undercut

**Head Diameter:**

Between 0.194 inches and 0.198 inches

**Head Height:**

Between 0.134 inches and 0.138 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.138 inches

**Width Across Flats:**

Between 0.0937 inches and 0.0952 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

170000 pounds per square inch

**Countersink Angle:**

20.0 degrees

**Surface Finish:**

32.0 microinches sides of head

**Product Name:**

Navy special project

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0