## NSN 5305-01-101-1412

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-101-1412 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.510 inches and 0.546 inches **Fastener Length:** Between 0.718 inches and 0.750 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.194 inches and 0.198 inches **Head Height:** Between 0.134 inches and 0.138 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.0937 inches and 0.0952 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 170000 pounds per square inch **Countersink Angle:** 20.0 degrees **Surface Finish:** 32.0 microinches sides of head **Product Name:** Navy special project Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response

N/a

Unc

Shelf Life:

**Thread Series Designator:** 

## NSN 5305-01-101-1412

Socket Head Cap Screw - Page 2 of 2



	• •						
ın	18	Of	ΝЛ	ດລ	CI.	ır	ο.

--

Demilitarization:

No

Fiig:

A003b0