NSN 5305-01-101-4814

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-101-4814 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.230 inches and 0.250 inches **Fastener Length:** Between 0.907 inches and 0.938 inches **Head Style:** Pan **Head Diameter:** Between 0.353 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **First Diameter From Head:** Between 0.125 inches and 0.130 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.657 inches and 0.708 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Product Name:** Navy special project Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 **Material Specification:** 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-101-4814

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0