NSN 5305-01-101-4836

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-101-4836 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.384 inches and 0.467 inches **Fastener Length:** Between 1.140 inches and 1.170 inches **Head Style:** Oval countersunk **Head Diameter:** Between 0.469 inches and 0.474 inches **Grip Diameter:** Between 0.3115 inches and 0.3120 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.678 inches and 0.698 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:**

Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

NSN 5305-01-101-4836

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0