## NSN 5305-01-101-4838

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-101-4838 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.251 inches and 0.301 inches **Fastener Length:** Between 1.073 inches and 1.103 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.328 inches and 0.376 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.802 inches and 0.822 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.1 degrees Surface Finish: 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams5737 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1153 professional/industrial association standard

Shelf Life:

N/a

## NSN 5305-01-101-4838

Close Tolerance Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0