## NSN 5305-01-101-5577

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-101-5577 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.188 inches **Fastener Length:** Between 0.658 inches and 0.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches **First Diameter From Head:** 0.102 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.470 inches and 0.562 inches **Internal Drive Style:** Cross recess type ii **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses **Surface Treatment:** Passivate threads **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response threads **Supplementary Features:** Altered item nsn5305-00-068-5415 rn 96906 ms16995-20 **Thread Series Designator:** Unc Shelf Life:

N/a

## NSN 5305-01-101-5577

Externally Relieved Body Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0