

View Online at <https://aerobasegroup.com/nsn/5305-01-101-6020>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.143 inches and 0.188 inches

**Fastener Length:**

Between 0.157 inches and 0.188 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.104 inches and 0.118 inches

**Head Height:**

Between 0.045 inches and 0.053 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.073 inches

**Thready Qty Per Inch (tpi):**

72

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Screw Material:**

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unf

**Specification Or Standard:**

1 type and 4s style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0