## NSN 5305-01-101-8141

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-101-8141

view offilite at https://aerobasegroup.com/hsh/osos-or-tor-or-r
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.303 inches and 0.328 inches
Fastener Length:
Between 1.375 inches and 1.385 inches
Head Style:
Pan
Head Diameter:
Between 0.357 inches and 0.373 inches
Head Height:
Between 0.122 inches and 0.133 inches
Shoulder Diameter:
0.193 inches first shoulder and 0.195 inches first shoulder
Shoulder Length:
1.052 inches first shoulder and 1.072 inches first shoulder
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Shoulder Shape:
Round first shoulder
Material:
Steel comp 4037 or steel comp 8630
Material Specification:
Ams 6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a

## NSN 5305-01-101-8141

Shoulder Screw - Page 2 of 2



Unit Of Mea	sure:
-------------	-------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6050 spec.