## NSN 5305-01-101-9436



Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-101-9436 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.320 inches and 0.370 inches **Fastener Length:** Between 1.018 inches and 1.048 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.337 inches and 0.383 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.678 inches and 0.698 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Material: Steel comp 4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 cl 2 federal specification single treatment response **Thread Series Designator:** 

Unjf Shelf Life:

N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5305-01-101-9436

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.