NSN 5305-01-102-1849



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-102-1849 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.376 inches and 0.451 inches **Fastener Length:** Between 0.579 inches and 0.624 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.452 inches and 0.510 inches **Head Height:** 0.073 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** 100.0 degrees **Screw Material:** Steel comp 4037 or steel comp 8740 **Screw Material Specification:** Astm a304 assn standard all material responses or astm a322 assn standard all material responses **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, type 1 cl 3 federal specification single treatment response **Special Features:** Furnished with one polytetrafluoroethylene washer and one silicone o-ring **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-102-1849 Machine Screw - Page 2 of 2



Fiig:

A500d0