

View Online at <https://aerobasegroup.com/nsn/5305-01-102-2656>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.370 inches and 0.380 inches

Fastener Length:

Between 0.370 inches and 0.380 inches

Head Style:

Watertight

Head Diameter:

0.168 inches

Head Height:

0.055 inches

Internal Drive Style:

Slot

Thread Diameter:

0.086 inches

Features Provided:

O ring

Thready Qty Per Inch (tpi):

56

Screw Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Screw Surface Treatment:

Passivate

Screw Surface Treatment Specification:

Qq-p-35 ty1 or ty2 or ty3 or ty4 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0