NSN 5305-01-102-2656

Machine Screw - Page 1 of 1

Demilitarization:

No Fiig: A500d0



View Online at https://aerobasegroup.com/nsn/5305-01-102-2656 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.370 inches and 0.380 inches **Fastener Length:** Between 0.370 inches and 0.380 inches **Head Style:** Watertight **Head Diameter:** 0.168 inches **Head Height:** 0.055 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.086 inches **Features Provided:** O ring Thready Qty Per Inch (tpi): 56 **Screw Material:** Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316 or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385 **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 ty1 or ty2 or ty3 or ty4 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**