

View Online at <https://aerobasegroup.com/nsn/5305-01-102-3615>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.631 inches and 0.681 inches

**Fastener Length:**

Between 1.266 inches and 1.296 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.612 inches and 0.672 inches

**Grip Diameter:**

Between 0.4365 inches and 0.4370 inches

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.438 inches

**Grip Length:**

Between 0.615 inches and 0.635 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

Dry film lubricant

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0