## NSN 5305-01-102-4367

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-102-4367 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.125 inches and 0.135 inches **Fastener Length:** Between 0.169 inches and 0.201 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.257 inches and 0.277 inches **Head Height:** 0.060 inches **First Diameter From Head:** 0.095 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.195 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Non-standard point 25 degree countersunk, 0.040 inch dia. And 0.195 inch nom. Length Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 **Material Specification:** 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** 

Unc

**Thread Series Designator:** 

Qq-p-35 federal specification single treatment response

## NSN 5305-01-102-4367

Externally Relieved Body Screw - Page 2 of 2



SI	1e	lf	Ιi	fe:
Ο.	···	•••	_,	٠٠.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0