Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-102-7322

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.359 inches and 0.491 inches
Fastener Length:
Between 1.230 inches and 1.270 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.547 inches and 0.577 inches
Head Height:
Between 0.234 inches and 0.266 inches
First Diameter From Head:
Between 0.170 inches and 0.180 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.739 inches and 0.911 inches
Internal Drive Style:
Slot
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Externally Relieved Body Diameter Quantity:
1
Special Features:
Straight knurl
Material:
Steel comp 304 or steel comp 303
Material Specification:
Qq-s-763 federal specification 1st material response or astm a582 assn standard 2nd material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0