NSN 5305-01-102-8456



Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-102-8456 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.381 inches and 0.431 inches **Fastener Length:** Between 1.079 inches and 1.109 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.3765 inches and 0.3813 inches **Head Height:** Between 0.0439 inches and 0.0459 inches **Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

Internal Drive Style:

High-torque

Thread Diameter:

0.190 inches

Grip Length:

Between 0.678 inches and 0.698 inches

Thready Qty Per Inch (tpi):

32

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Surface Finish:

32.0 microinches threads

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Aluminum and chromate

Surface Treatment Specification:

Mil-c-83488 type 2 cl 3 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5305-01-102-8456

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.