## NSN 5305-01-102-9840

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-102-9840

| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| Between 0.381 inches and 0.431 inches                                    |
| Fastener Length:   |
| Between 0.953 inches and 0.983 inches                                    |
| Head Style:  |
| Oval countersunk   |
| Head Diameter:   |
| Between 0.2966 inches and 0.3016 inches                                  |
| Grip Diameter:   |
| Between 0.1885 inches and 0.1895 inches                                  |
| Internal Drive Style:  |
| High-torque  |
| Thread Diameter:   |
| 0.190 inches   |
| Grip Length:   |
| Between 0.552 inches and 0.572 inches                                    |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Countersink Angle:   |
| 101.0 degrees  |
| Material:  |
| Steel comp xm-13   |
| Material Specification:  |
| Ams 5629 assn standard single material response                          |
| Surface Treatment:   |
| Aluminum and chromate  |
| Surface Treatment Specification:   |
| Mil-c-83488 type 2 cl 3 military specification single treatment response |
| Thread Series Designator:  |
| Unjf   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A003b0   |
|  |

NSN 5305-01-102-9840

Close Tolerance Screw - Page 2 of 2

Mil-std (military Standard):

Mil-c-83488 spec.

