

View Online at <https://aerobasegroup.com/nsn/5305-01-103-1766>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.418 inches and 0.458 inches

Fastener Length:

Between 0.788 inches and 0.808 inches

Head Style:

Fillister countersunk

Head Diameter:

Between 0.3898 inches and 0.3948 inches

Head Height:

0.015 inches

Grip Diameter:

Between 0.2485 inches and 0.2495 inches

Internal Drive Style:

High-torque

Thread Diameter:

0.250 inches

Grip Length:

Between 0.350 inches and 0.370 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

125000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Stainless steel

Material Specification:

23112, ty d, fscm 76301 mfr ref single material response

Surface Treatment:

Aluminum and chromate

Surface Treatment Specification:

Mil-c-83488 type 2 cl 3 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.