NSN 5305-01-103-4155

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-103-4155 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.140 inches **Fastener Length:** 0.325 inches **Head Style:** Fillister **Head Diameter:** 0.173 inches **Head Height:** 0.098 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Hardness Rating:** 36.0 rockwell c and 38.0 rockwell c **Primary Washer Outside Diameter:** 0.172 inches **Primary Washer Style:** Flat **Primary Washer Material Thickness:** Between 0.020 inches and 0.026 inches Material: Steel comp 4130 **Material Specification:** Mil-s-6758 cond c and 4 military specification single material response **Surface Treatment:** Passivate head **Surface Treatment Specification:** Mil-f-14072 -262a military specification single treatment response head **Thread Series Designator:** Unc

Shelf Life: N/a

NSN 5305-01-103-4155

Assembled Washer Screw - Page 2 of 2



П	Init	7 1+	Measure:
u	,,,,,	v	wicasuic.

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.